



AZUSA'S FIVE INCH ALUMINUM SPLIT-RIM WHEELS

- ✓ Classic "TRI STAR" Design
- ✓ Bead-Biting Edges Prevent Slipping
- ✓ Split Rim for Easy Tire Mounting
- ✓ Beautiful Ball-Burnished Finish
- ✓ Grade 5 Hardware
- ✓ 3.75" Bolt Circle



5" ALUMINUM "TRI STAR" WHEELS - 3" Wide	
BALL BEARING WHEEL (BB)	Part No.
With 5/8" ID Prec Ball Bearings	1144
With 5/8" ID Std Ball Bearings	1146
With 3/4" ID Std Ball Bearings	1148
Two Halves w/Nuts & Bolts Only	1145
One Half Only	8053
TAPERED ROLLER BEARING WHEEL (TRB)	
With 5/8" ID Sealed TRB*	1135
With 3/4" ID Sealed TRB*	1136
With 3/4" ID TRB	1137
With 5/8" ID TRB	1138
With Races, Nuts & Bolts Only	1139
Two Halves w/Nuts & Bolts Only	1142
One Half Only	8052
<i>Dust shields provided w/TRB wheels except *</i>	
LIVE AXLE WHEEL	
With Steel Insert-1" to 3/4" Step	1147
Half w/Steel Insert 1" ID, 1/4" Keyway	8054
With (2) 8054 Halves-Complete	1149
Half with 3/4" Bore	8052

See [page 10](#) for Complete Wheel Dimensions

See [page 8](#) for 5" Wheel Accessories

THE FOLLOWING TIRES WILL FIT THESE WHEELS

340/300 x 5	Sawtooth Tread
410/350 x 5	Sawtooth Tread
11-400 x 5	Turf Saver tread
11-400 x 5	Ribbed Tread
410/350 x 5	Studded Tread
10-450 x 5	Slick, Regular
340/300 x 5	Slick, Narrow
340/300 x 5	Slick, Regular
410/350 x 5	Slick, Regular
11-350 x 5	Slick, Regular
11-450 x 5	Slick, Regular
11-360 x 5	Slick, Heavy Duty
12-400 x 5	Slick, Heavy Duty

See [page 12](#) & [page 13](#) for Tire & Tube Part Numbers

TIRE TREAD PATTERNS

